

Product code

010-0052

Part Number

MODULO RFID MFRC522 - 13,56 MHZ

Product description

MODULO RFID MFRC522 - 13,56 MHZ

Main features

1. 13.56Mhz RFID module Kit with IC card and round key chain tag. SPI interface fo convenient interface to microcontrollers such as Arm/AVR/Pic/Arduino, etc.
2. The RFID Reader Module can be used in a wide variety of hobbyist and commercial applications, including access control, automatic identification, robotics, navigation, inventory tracking, payment systems, and car immobilisation.

Technical specifications

Supply Voltage : 3.3V  
Current : 13-26mA  
Operating frequency: 13.56MHz  
Read Range: 0 -60mm (mifare 1 card)  
Interface: SPI ,Data Transfer Rate: Max 10Mbit /s  
Dimensions: 40mm × 60mm  
Size of Round Tag : 0.87 × 85.5 × 54 mm  
Size of Rectangle Tag : 32 x 40.5 x 4.2 mm  
Supported card types:  
mifare1 S50, the mifare1 S70,  
  
Mifare UltraLight, Mifare Pro, mifare DESFire  
  
Environmental Operating temperature: -20 to 80 Celsius degree.  
Environmental Storage Temperature: -40 to 85 Celsius degree.  
Relative humidity: relative humidity 5% to 95%.

Packing list

1 X RFID-RC522 module one  
1 X Standard S50 Blank Card  
1 X S50 shaped cards one (as shown keychain shape)  
1 X Straight row pin  
1 X Curved row pin

Dimensions

8,5x5,5x1,0mm

Weight

21g